



Tender specification:

All doors comply with the following standards and regulations:

**Lift Directive 2014/33/EU
EN 81-20/50**

**Swing landing door, single panel, side opening with concealed hinges
with glass door panel framed on all sides**

Frame: folded sheet steel, 2 mm thick, primed, circumferential 120 mm wide

Door panel: folded sheet steel, 1.5 mm thick, primed

Sill: folded sheet steel, 4.0 mm thick, primed

Window: large-area, glazing with laminated safety glass 5+5 mm with film 0.76 mm

Window frame: of steel primed, concealed fastening

Locking / closing mechanism: ATS tubular door closer

Interlock: Kronenberg interlock DLF 1, roller lever mounted on the interlock, release direction toward the door panel, roller lever actuation parallel to the frame and sill, position of interlock in the closing frame

Emergency release: according to EN 81-20 400 mm above finished floor level

Options:

Protection class: Interlock and door contacts at least IP 54

Powder coating: Door panel and frame, powder coated on all sides according to RAL

Stainless steel cladding: Door panel two-sided, door frame landing side clad with stainless steel, 1.4301 (AISI 304)

Door panel and door frame: manufactured completely of stainless steel 1.4301 (AISI 304) / 1.4571 (AISI 316), glass-bead blasted